Solar MD

Leaders in Energy Storage Solutions

NEW Battery Range



NEW Cell Facts

CATL

CB2W0

Operating Voltage: 2.5 – 3.65V
 Typical Capacity: 280Ah
 Max Charge Power: 1C

Cycle Performance: 6000 Cycles

• Dimensions: 207.2 x 173.9 x 71.7 (+/-0.8)

CBC00

Operating Voltage: 2.5 – 3.65V
 Typical Capacity: 314Ah
 Max Charge Power: 0.5C

• Cycle Performance: 7000 Cycles

• Dimensions: 204.44 x 174.26 x 71.55 (+/-0.8)



→NEW Battery Range | From 01. July

NEW Batteries:

Low Voltage

- SS4143 **NEW SS4160**
- SS214 NEW SS216



High Voltage

• SS6143 **NEW SS6160**



16 kWh Capacity in the SAME size

Key benefits include:

- Increased Capacity: Now 16 kWh per unit.
- Extended Cycle Life: Up to 7,000 full cycles.
- **Lower Cost per kWh:** Delivering a superior return on investment for your customers.
- Higher Throughput Guarantee: A robust 84 MWh guarantee.





Feature: SS4160/SS216/SS6160

Rated Capacity	16 kWh
Nominal Power	8 kW
Charge and Discharge Current:	157A
Nominal Voltage	51.2V
Energy Throughput	84 MWh
Cycle Life Design	7,000 Cycles

Upgrade with EASECompatible with all previous batteries

Low Voltage Upgrade

NO restrictions

High Voltage Upgrade

- Charging and discharging current reduced to 157A of a full HV stack.
- Capacity reduced from 16 to 14.3kWh



UPGRADE WITH EASE

Compatible with all older modules

MORE Power, Same Space
All batteries are built into the same metal housing

- NO restrictions
- Same housing
- Same cabling
- Same racks




MORE Cycles, **LONGER** Life 84MWh Energy Throughput Guarantee

- More reliable performance
- More return of investment
- More peace of mind



GET SCALABLE POWER RANGING FROM 80 kWh to 272 kWh **Standalone Bundle Bundle** 80 - 272 kWh 100kW / 208 kWh 125kW / 272kWh

HIGH VOLTAGE RANGE



40FT BESS CONTAINERS

reach a massive **6.5 MWh** of storage capacity, utilizing 408 individual SS6160 modules.

Thank you!